


Web [Images](#) [Maps](#) [News](#) [Video](#) [Gmail](#) [more](#) ▼



[Sign in](#)

negative and acknowledgement and packet and payload

Search

[Advanced Search](#)
[Preferences](#)

Results - 10 of about **190,000** for negative and acknowledgement and packet and payload. (0.16 seconds)

1. [Immediate **negative acknowledgement** for a communication network ...](#)

accepting the data **packet** when the data **payload** does not have an error; and immediately sending a **negative acknowledgement** to the transmitting node when the ...

www.patentstorm.us/patents/6640325/claims.html - [Similar pages](#)

2. [Sender-initiated recovery algorithm \(SIRA\) for the layer 2 ...](#)

Aug 1, 2006 ... The L2TP sender transmits a **payload** message that includes the "Reset ... Nr value represents a **negative acknowledgement**; and initiating a recovery ... A **packet** interface for use in forming a layer 2 tunneling protocol ...

www.freepatentsonline.com/7085273.html - [Similar pages](#)

by MC Chuah - 2006 - [Related articles](#) - [All 6 versions](#)

3. [RTP **payload** format for H.261 video streams](#)

Turletti & Huitema Standards Track [Page 1] RFC 2032 RTP **Payload** Format **Negative ACKnowledgements (NACK) packet** The format of the NACK **packet** is as ...

www.isi.edu/in-notes/rfc2032.txt - 28k - [Cached](#) - [Similar pages](#)

4. [VPN Tunnels - GRE Protocol 47 **Packet** Description and Use](#)

Set to one (1) if a **payload** || S | (data) **packet** is present. Set to zero (0) if **payload** is not || | present (GRE **packet** is an **Acknowledgment** only). ...

support.microsoft.com/kb/241251 - [Similar pages](#)

5. [RFC 2032 \(rfc2032\) - RTP **Payload** Format for H.261 Video Streams](#)

The purpose of this memo is to specify the RTP **payload** format for **Negative ACKnowledgements (NACK) packet** The format of the NACK **packet** is as follow: ...

www.faqs.org/rfcs/rfc2032.html - 30k - [Cached](#) - [Similar pages](#)

6. [esp@cenet — Bibliographic data](#)

The overlay transceiver apparatus further (100) comprising a **packet** ... (136) in the **payload** portion (117) of the **acknowledgement data packet** (135), ...

v3.espacenet.com/textdoc?DB=EPODOC&IDX=EP1871045 - 44k

- [Cached](#) - [Similar pages](#)

by I AAD - 2007 - [All 3 versions](#)

7. [Rx protocol specification draft Nickolai Zeldovich, kolya@MIT.EDU ...](#)

Oct 20, 2002 ... There is no **payload** associated with an **acknowledge-all packet**.
can be as follows: 0 Explicit **negative acknowledgement: packet** with the ...
web.mit.edu/kolya/afs/rx/rx-spec - [Similar pages](#)

8. [Bluetooth operation and use - Google Books Result](#)


by Robert K. Morrow - 2002 - Technology & Engineering - 567 pages
A baseband **packet payload** can have as many as 2745 bits, which includes a ... slot if
the **packet** is good; otherwise, it returns a **negative acknowledgment** ...
books.google.com/books?isbn=007138779X...

9. [GRE, Generic Routing Encapsulation](#)

Set if a **payload packet** is present. Cleared if a **payload packet** is not present (GRE
packet is an **Acknowledgment** only). s, Strict Source Route. 1 bit. ...
www.networksorcery.com/enp/protocol/gre.htm - 13k - [Cached](#) - [Similar pages](#)

10. [\file halfMacClient.c \brief Half MAC Workshop Exercise. @version ...](#)

... to hold received **packet** Macframe rxBuffer; ///Data **packet** with **payload** ...
DATAPACKET 1 ///**Acknowledgement packet** meant for halting retransmissions ...
warp.rice.edu/svn/WARP/ResearchApps/MAC/HALFMAC/halfMacClient.c - 11k
- [Cached](#) - [Similar pages](#)



negative and acknowledgement and packet and payload

Search

[Search within results](#) - [Language Tools](#) - [Search Help](#) - [Dissatisfied? Help us improve](#) - [Try Google Experimental](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [Privacy](#) - [About Google](#)